

# HSGM

## STYROFOAM-CUTTERS

### Type HSGM STYRO-CUT 140

The powerful performance professional tool for the Building Trade.  
For board thicknesses **up to 140 mm (5.5")** and for specialty cuts.

#### Technical Description:

Heats up in only 10 seconds  
Supply voltage: 230V-50Hz (black housing)  
110V-60Hz (yellow housing)  
Power input: 110 Watt  
Intermittent operation: 1/4 min.  
Protective insulation  
3 m electric cord with 2-pin straight plug  
Blade temperature 500°C (930°F) max.  
Eliminates styrofoam dust  
Gewicht: 1025 g (with blade)



#### Basic Kit:

- 1 HSGM-STYRO-CUT 140
- 1 Blade type C-140, for boards up to 140 mm.
- 1 Suspension hook
- 1 Operating instructions
- 1 Carton package (also available in a plastic case)

#### Practicable blades:

Type C-100  
For boards  
up to 100 mm (4")



Type C-140  
For boards  
up to 140 mm (5.5")



Type CN-14, curved,  
For 14 mm grooves



Type CN-20, curved,  
For 20 mm grooves




Type CN-26, curved,  
For 26 mm grooves



Type CR-20, curved,  
For 20 mm grooves  
with depth-guide



Type CS-20, square-type,  
For 20 mm grooves  
with depth-guide



Type CV-20, V-type,  
For 20 mm grooves  
with depth-guide

